



TECHNICAL SHEET

OPERATIONAL DATA

FT AIRLESS OIL BOTTLE
Elaboration date: 01/14/2023
Revision: 05/23/2025-04



AIRLESS OIL BOTTLE

References 279 (300ml) / 280 (500ml) / 281 (1000ml)

DESCRIPTION

Contains mineral base oils and anti-wear additives for the lubrication of hydraulic systems.
It offers protection against rust and corrosion.
Available in the following volumes:
- 300ml - code 279 / 500ml - code 280 / 1000ml - code 281

BENEFITS TO THE CONSUMER:

EXTENDS THE EQUIPMENT'S LIFESPAN - thanks to its anti-wear package that helps reduce friction between moving parts;
Protects against rust and corrosion - contains inhibiting additives that contribute to the protection of metal surfaces;

Allows for easy removal of water from circulatory systems;

LOW FOAM FORMATION AND RAPID AIR RELEASE
- ensuring the proper operation of the equipment.



PACKAGING MEASUREMENTS	HEIGHT	LENGTH	WIDTH
300ml	7cm	22cm	7cm
500ml	8cm	24cm	8cm
1.000ml	9,5cm	31cm	9,5cm

INDICATIONS FOR USE

Suitable for lubricating hydraulic systems, especially those operating above 1000 psi pressure and over 1200 rpm. Also indicated for compressors and electric motors that require a product with these viscosity grades and anti-wear properties.

ADDITIONAL DATA

MAX. OPERATING PRESSURE	5.000 PSI
GROSS WEIGHT 300ML	0,32kg
GROSS WEIGHT 500ML	0,54kg
GROSS WEIGHT 1000ML	1,1kg



Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br