



TECHNICAL SHEET

OPERATIONAL DATA

FT N-18 - 795
Elaboration date: 01/14/2023
Revision: 05/23/2025-03

NAUBER[®]
MAQUINAS AIRLESS INDUSTRIAL

N-18 MEMBRANE PUMP

Reference 795

DESCRIPTION

High capacity, lightweight and compact fluid transfer pump.



High-quality PTFE membrane that, due to its large diameter, generates a large output volume and extends the equipment's useful life.

FEATURES

Dual coil air valve.

High precision paint pressure regulator and return regulator.

Low and high collector with enlarged internal diameter for easier cleaning and inspection.



INDICATIONS FOR USE

Suitable for painting, chemicals, oil, fluid transfer, etc.

| | HEIGHT | LENGTH | WIDTH |
|----------------------|--------|--------|-------|
| PACKAGING DIMENSIONS | 29cm | 48cm | 42cm |

ADDITIONAL DATA

| | |
|---------------------------|-----------------------|
| MAX. TRANSFER CAPACITY | 18 LITERS/MIN. |
| MAXIMUM AIR PRESSURE | 7,0 bar |
| INPUT OUTPUT OF MATERIAL | 3/8" NPT |
| AIR INLET AND OUTLET SIZE | 1/4" NP |
| MAX GRAIN SIZE | 1,5mm |
| AIR CONSUMPTION | 150 LITERS/MIN. |
| GROSS WEIGHT | 7,2kg |
| COMPRESSOR INDICATION | 7 bar/10 ft flow rate |



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br