



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5/SMART 1600 - 5814
Elaboration date: 08/05/2026
Revision: 00/00/0000-00



ROTO-5 SANDER KIT WITH SMART 1600 VACUUM CLEANER

Reference 5814

DESCRIPTION

Kit consisting of the **ROTO-5 sander** and the **SMART 1600 vacuum cleaner**.

Random orbital sander with brushless motor. Equipped with a 350-watt motor. Electronic speed adjustment, ranging from 4,000 RPM to 10,000 RPM.

The Nauber SMART 1600 vacuum cleaner is a lightweight and compact vacuum cleaner for professional use, ideal for vacuuming dust and liquids.



CHARACTERISTICS

LX-E GIRAFFE SANDER

Braking assistance system with swivel on the suction hose. Integrated electrical stabilizer. Working memory (stores the last speed setting). 6" / 150mm diameter base plate with multi-hole pattern. Power cord, 5 meters long.

Equipment operates on 220V / 50-60Hz.

SMART 1600 VACUUM CLEANER

Equipped with a 1600W motor, AUTO-START system (the vacuum cleaner will automatically turn on when connected), and AUTO-CLEAN system (automatic filter cleaning at programmed intervals) maintaining constant suction power and extending the equipment's lifespan. It has a 30-liter capacity reservoir. Includes a remote control. Features a handle and locking casters for easy transport. Low noise level. Compact and easy to carry.

Equipment operates on 220 volts/50-60Hz.

	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS	64,5cm	45,8cm	37,5cm

INDICATIONS FOR USE

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, finishing compounds, and general decorative effects.

ADDITIONAL DATA	
GROSS WEIGHT	18,60kg
GENERATOR/TRANSFORMER INDICATION	5kVA



Assembled in Brazil



Record 172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5/SMART 1600 - 5814
Elaboration date: 08/05/2026
Revision: 00/00/0000-00

NAUBER[®]

MAQUINAS

ROTO-5 SANDER KIT WITH SMART 1600 VACUUM CLEANER

Reference 5814

ROTO-5 SANDER

ADDITIONAL DATA	
ENGINE POWER	350W
ROTATION	4.000-10.000 RPM
ECCENTRICITY	5mm
BASE DIAMETER	6" / 150mm
APPROXIMATE MASS	1,4kg
NET WEIGHT	2,25kg
GROSS WEIGHT	2.41kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER INDICATION	2 kVA



SMART 1600 VACUUM CLEANER

ADDITIONAL DATA	
ENGINE POWER	1600W
SUCTION POWER	25 kPa
POT. NOMINAL TOMADA AUX.	2000W
FLOW RATE	1.7m ³ /min.
PROTECTION CLASS	IPX4
NOISE	82dB
NET WEIGHT	12.75kg
GROSS WEIGHT	16,19kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER	3kVA



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br