



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5E/APN-1600 - 4735
Elaboration date: 08/13/2025
Revision: 10/21/2025-01

NAUBER[®]

MAQUINAS

ROTO-5E SANDER KIT WITH APN-1600 VACUUM CLEANER

Reference 4735

DESCRIPTION

Kit consisting of the **ROTO-5E Brushless Sander** and the **APN-1600 Vacuum Cleaner**.

Random orbital sander with brushless motor.
Equipped with a 350-watt motor.
Digital panel with electronic speed adjustment, ranging from 4,000 RPM to 10.000 RPM.

The Nauber APN-1600 vacuum cleaner is a lightweight and compact vacuum cleaner for professional use, ideal for vacuuming dust and liquids.



FEATURES

ROTO-5E Brushless Sander

Integrated electrical stabilizer.
Working memory (stores the last speed setting used).
6" / 150mm diameter base plate with multi-hole pattern.
Approximate weight of 1.45 kg (without the power cord).
Power cord, 5 meters long.

220V / 50-60Hz equipment.

APN-1600 Vacuum Cleaner

Made from high-strength plastic material. Equipped with a 1600W motor, auto-start system (when the connected device is plugged in, the vacuum cleaner will automatically turn on). It has a 30-liter capacity dustbin. It features a handle and wheels for easy transport.

220V / 50-60Hz equipment.

	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS	59cm	84cm	48cm

INDICATIONS FOR USE

Ideal for use in construction or for general cleaning.

ADDITIONAL DATA	
GROSS WEIGHT	21.90kg
GENERATOR/TRANSFORMER	5kVA



Assembled in
Brazil



CREA-SC
Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-5E/APN-1600 - 4735
Elaboration date: 08/13/2025
Revision: 10/21/2025-01

NAUBER[®]

MAQUINAS

ROTO-5E SANDER KIT WITH APN-1600 VACUUM CLEANER

Reference 4735

ROTO-5E BRUSHLESS SANDER

ADDITIONAL DATA	
ENGINE POWER	350W
ROTATION	4.000-10.000 RPM
ECCENTRICITY	5mm
BASE DIAMETER	6" / 150mm
NET WEIGHT	1,65kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER	2kVA



APN-1600 Vacuum Cleaner

ADDITIONAL DATA	
ENGINE POWER	1600W
SUCTION POWER	20 kPa
POT. NOMINAL TOMADA AUX.	2000W
FLOW RATE	1.6m ³ /min.
PROTECTION CLASS	IPX4
NOISE	82dB
NET WEIGHT	13,5Kg
VOLTAGE	220V - 50/60Hz
GENERATOR/TRANSFORMER	3kVA



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br