



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-6X - 4812
Elaboration date: 09/16/2025
Revision: 10/21/2025-03



ROTO-6X ROTO-ORBITAL BRUSHLESS SANDER

Reference 4812

DESCRIPTION

Roto-orbital sander with a 350W brushless motor, offering high performance and low maintenance. New anatomical design that provides better ergonomics and less fatigue during prolonged use. Electronic speed adjustment, ranging from 4,000 RPM to 10,000 RPM.

FEATURES

Braking assistance system with a swivel on the suction hose, ensuring greater safety and control. Integrated electronic stabilizer, maintaining constant rotation even under load. Working memory, which stores the last speed setting used. 6"/150mm multi-hole base plate, optimizes dust extraction and improves finish. Eccentricity rate of 5mm, ideal for efficient and uniform sanding. 5m power cord, removable via direct plug, offering greater reach, convenience and easy replacement.

220V / 50-60Hz equipment.



With carrying case for transport and storage.

INDICATIONS FOR USE

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, finishing compounds, and general decorative effects.

ADDITIONAL DATA

ENGINE POWER	350W
ROTATION	4.000-10.000 RPM
Eccentricity rate	5mm
BASE DIAMETER	150mm/6"
NET WEIGHT	1.23kg
GROSS WEIGHT (Packaging)	2,85kg
GENERATOR/TRANSFORMER	2kVA



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br