



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-9X - 4811
Elaboration date: 09/16/2025
Revision: 10/31/2025-03



ROTO-9X GIRAFFE ROTO-ORBITAL SANDER

Reference 4811

DESCRIPTION

Nauber ROTO-9x Brushless Roto-Orbital Sander for ceilings and walls. Designed to offer superior finish and high efficiency, the ROTO-9x features a 400W brushless motor, ensuring durability, low maintenance, and consistent performance.

The 225mm multi-hole base plate, combined with the structure and internal channels, was developed to optimize the extraction of debris by the external vacuum cleaner, eliminating the need for side brushes and providing an impeccable finish with minimal effort, while also keeping the environment clean.

FEATURES

Roto-orbital system, providing uniform and efficient sanding.

Optimized suction design, developed for use with an external vacuum cleaner.

Multi-hole pad that enhances dust extraction and increases sandpaper performance.

Without side bristles, greater suction efficiency and a higher quality finish.

Brushless motor (without carbon brushes), longer lifespan and greater reliability.

Super flexible hose with a reach of up to 4 m.

Carrying bag and storage.

220V / 50-60Hz equipment.

INDICATIONS FOR USE

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, cementitious and finishing compounds.

ADDITIONAL DATA	
ENGINE POWER	400W
ROTATION	4.000-8.500 RPM
ECCENTRICITY RATE	4mm
BASE DIAMETER	225mm
NET WEIGHT	3,2kg
GROSS WEIGHT (Packaging)	7,8kg
GENERATOR/TRANSFORMER	2kVA



PACKAGING MEASUREMENTS	HEIGHT	LENGTH	WIDTH
	19.75cm	153cm	26cm



Email

atendimento@nauber.com.br



Telephone

+55 47 33745969



Web Site

www.nauber.com.br