



TECHNICAL SHEET

OPERATIONAL DATA

FT ROTO-9X - 4811
Elaboration date: 09/16/2025
Revision: 05/26/2026-05



GIRAFFE ROTARY ORBITAL SANDER ROTO-9X

DESCRIPTION

Nauber ROTO-9x Brushless Rotary Orbital Sander for ceilings and walls. Designed to offer superior finish and high efficiency, the ROTO-9X features a 400W brushless motor, ensuring durability, low maintenance, and consistent performance.

The 225mm multi-hole base plate, combined with the structure and internal channels, was developed to optimize the extraction of debris by the external vacuum cleaner, eliminating the need for side brushes and providing an impeccable finish with minimal effort, while also keeping the environment clean.

CHARACTERISTICS

Rotary-orbital system, providing uniform and efficient sanding. Optimized suction design, developed for use with an external vacuum cleaner.

Multi-hole pad that enhances dust extraction and increases sandpaper performance.

No side bristles, greater suction efficiency.

- and quality in the finish.

Brushless motor (no carbon brushes), longer lifespan.

- Useful and reliable.

Super flexible hose with a reach of up to 4 m.

- Carrying bag and storage.

Equipment operates on 220V / 50-60Hz.

Reference 4811



HIGH POWER LED LIGHT

225mm 9" Standard Multi-Hole Base

SUPER FLEX HOSE THAT REACHES UP TO 4M IN LENGTH

	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS	19.75cm	153cm	26cm
TOTAL LENGTH OF THE SANDER			1.45m

INDICATIONS FOR USE

Ideal for sanding joint compound, acrylic filler, plaster, masonry, wood, cementitious and finishing compounds.

ADDITIONAL INFORMATION	
ENGINE POWER	400W
ROTATION	4.000-8.500 RPM
ECCENTRICITY RATE	4mm
BASE DIAMETER	225mm
NET WEIGHT	3,2kg
GROSS WEIGHT (Packaging)	7,8kg
GENERATOR/TRANSFORMER	2kVA



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br