



TECHNICAL SHEET

OPERATIONAL DATA

FT LXR850-CS - 1166
Elaboration date: 14/01/2023
Revision: 24/05/2025-03

NAUBER[®]
MAQUINAS

LXR850-CS GIRAFFE SANDER

Reference 1166

DESCRIPTION

Nauber LXR850-CS ceiling and wall sander with adjustable LED light. Equipped with an 850-watt motor. Self-priming - vacuums up to 90% of debris, eliminating the need for a vacuum cleaner. Articulated suction base, with 6 holes for better dust suction and sanding performance.



TRIGGER ACTUATION



FEATURES

It features a cable folding system for transport. The trigger actuation system features electronic speed adjustment, which ranges from 800 RPM to 1,700 RPM. Includes dust collection bag with a capacity of up to 30 liters.

220V / 50-60Hz Equipment

INDICATIONS FOR USE

Suitable for sanding masonry, plaster and putty walls.

	HEIGHT	LENGTH	WIDTH
PRODUCT DIMENSIONS	34cm	1.3m	74cm
PRODUCT DIMENSIONS WITH EXTENDER	34cm	1.65m	74cm
PACKAGING DIMENSIONS	34cm	24cm	74cm

ADDITIONAL DATA

POWER	850W
ROTATION	800-1.700 RPM
BASE DIAMETER	225mm
NET WEIGHT	4,5kg
GROSS WEIGHT	10,25kg
GENERATOR/TRANSFORMER	2 kVA



Assembled in
BRAZIL



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br