



TECHNICAL SHEET

OPERATIONAL DATA

FT D-6X LINE - 4805
Elaboration date 09/02/2025
Revision: 05/06/2026-02



D-6X LINE ROAD MARKING MACHINE

Reference 4805

DESCRIPTION

Road marking equipment with two spray guns, diaphragm system. Equipped with a 210cc, 4-stroke gasoline Nauber engine. Spray gun operation via the handlebars.

CHARACTERISTICS

Internal combustion engine.

High pressure for excellent spraying, better atomization, and greater efficiency and finish. Equipped with 2 Ultra model airless spray guns.

Max Kit paint reservoir with a capacity of up to 30 liters.

It features high-quality valves, a pressure regulator, and a mechanical pressure control valve.

It has a cart with accessories and a laser guide.

Includes 02 Nauber Ultra spray gun.

02 Light Green aluminum tip guard,

02 Light Green 215 airless tip and 01 15m hose.

Maximum hose length: 90 meters.



INDICATIONS FOR USE

Ideal for marking curbs, single and double lanes, parking lots, continuous and intermittent lines.

This equipment supports the use of low and medium viscosity materials, due to its pump capacity and motor power.

This equipment can be used for conventional airless painting.

	HEIGHT	LENGTH	WIDTH
PACKAGE MEASUREMENTS	102cm	122cm	74cm

ADDITIONAL INFORMATION	
ENGINE POWER	7,0 hp
MAXIMUM FLOW RATE	6.0 LITERS/MIN.
MAXIMUM AIRLESS TIP SIZE	0,037"
MAXIMUM PRESSURE	3.000 PSI
NET WEIGHT	67,5kg
GROSS WEIGHT	92,5kg
SUPPLY	GASOLINE



Assembled in Brazil



Record 172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br