



TECHNICAL SHEET

OPERATIONAL DATA

FT MPP-800 - 3711
Elaboration date: 01/13/2023
Revision: 07/25/2025-05



MPP-800 AIRLESS MACHINE

Reference 3711

DESCRIPTION

Airless painting and filler application machine with piston pump, with a flow capacity of up to 8.5 liters/min, simplified maintenance system and high-performance parts.

FEATURES

Motor brushless de 6,7 hp.
Equipped with a transport cart and an X-9 voltage controller module. 220 volt/50-60Hz equipment.

INCLUDED ITEMS:

01 Ultra spray gun;
01 517 airless tip for painting;
01 airless tip 529 for putty;
01 30 mesh filter;
01 60 mesh filter;
15 meters of 3/8 hose;
01 light green aluminum tip guard;
01 extensor 50cm;
01 user manual;
02 fixed wrenches 17/19mm;
01 set of fuses;
01 Philips screwdriver;
01 filter screen.

PRODUCTIVITY

Average productivity based on 8 hours of work:
- 1,500m² of painting (01 operator);
- 3,000m² of painting (02 operators);
- 1,000m² of filler (02 operators).

EQUIPPED WITH
CONTROLLER MODULE
VOLTAGE X-9



HOW MANY METERS OF HOSE
CAN I WORK WITH THE
MPP-800?

MATERIAL	SPRAY GUNS AMOUNT	DIRECTION	DISTANCE
PAINT	1	HORIZONTAL	90 METERS
	2	HORIZONTAL	45 METERS
	1	VERTICAL	45 METERS
	2	VERTICAL	22,5 METERS
PUTTY	1	HORIZONTAL	45 METERS
	1	VERTICAL	22,5 METERS

	HEIGHT	LENGTH	WIDTH
PACKAGING DIMENSIONS	89,5cm	69,5cm	66cm

INDICATIONS FOR USE

Suitable for general painting, acrylic paints, enamels, latex, epoxy, STAINLESS STEEL, acrylic putty and other medium density materials.

MONITOR:

VOLTAGE



TEMPERATURE



AMPERAGE



ADDITIONAL DATA

ENGINE POWER	6,7 hp
MAXIMUM FLOW RATE	8.5 LITERS/MIN.
MAX TIP SIZE	0,047"
MAXIMUM PRESSURE	22 MPa
VOLTAGE	220 VOLTS/50-60Hz
GROSS WEIGHT	66,4kg
GENERATOR/TRANSFORMER	8 kVA



Assembled in
BRAZIL



Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br