



TECHNICAL SHEET

OPERATIONAL DATA

FT D-3X MAX - 3701
Elaboration date: 01/13/2023
Revision: 23/08/2025-07



D-3X MAX AIRLESS MACHINE

Reference 3701

DESCRIPTION

Made of steel, treated with a galvanized process (anti-rust) and powder coated. The coupling connection to the machine is made of stainless steel. Equipped with a 220-volt induction motor. The shielded motor, with reliable power and performance, generates high production capacity. High pressure for an excellent finish, better atomization, and greater efficiency.

RESERVOIR DESCRIPTION

Made of PVC, with a capacity of up to 30 liters.

ADVANTAGES:

- Ease of suction;
- Possibility of placing 02 spray guns.

FEATURES

It features heavy-duty wheels for easy transport. It features high-quality valves, a pressure regulator, and a mechanical pressure control valve. The coupling to the machine is made of stainless steel. It has a reservoir with a capacity of up to 30 liters of material.

Includes 11/4 15m hose, 1 Nauber Ultra spray gun, 1 Light Green 517 airless tip, 1 Light Green aluminum tip guard, 1 filter 60 mesh and 1 extensor 50cm.

Maximum hose length: 60 meters.

220 volts/50-60Hz equipment.

INDICATIONS FOR USE

Residential and commercial projects, latex paints, acrylics, enamels, varnishes, sealers, PU.

Not suitable for industrial use.



	HEIGHT	LENGTH	WIDTH
PACKAGING DIMENSIONS	86cm	49cm	61cm

ADDITIONAL DATA	
ENGINE POWER	1.300W - 1,8 hp
MAXIMUM FLOW RATE	3.6 LITERS/MIN.
MAX TIP SIZE	0,025"
MAXIMUM PRESSURE	3.000 PSI
VOLTAGE	220 VOLTS/60Hz
GROSS WEIGHT	43,5kg
GENERATOR/TRANSFORMER INDICATION	5 kVA



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br