



TECHNICAL SHEET

OPERATIONAL DATA

FT D-3X - 4300
Elaboration date: 13/01/2023
Revision: 11/13/2025-08



AIRLESS MACHINE D-3X

Reference 4300

DESCRIPTION

Airless sprayer with a diaphragm system, recognized as the most durable on the market. It features a machined stainless steel head and a high-performance, shielded motor for long workdays.

Provides stable high pressure, excellent finish, better atomization and greater efficiency.

FEATURES

It features heavy-duty wheels for easy transportation, heavy-duty mechanical valves, a high-precision pressure regulator, a display with a mains voltage indicator, and a thermal protection relay.

Stainless steel outlet connection.

Includes 01 1/4" 15m hose, 01 Nauber Ultra spray gun, 01 Light Green 517 airless tip, 01 Light Green aluminum tip guard, 01 white 60 mesh filter and 01 50cm extender.

Maximum hose length:

60 meters (horizontal) and 30 meters (vertical).

220 volts/50-60Hz equipment.

INDICATIONS FOR USE

Suitable for construction use with acrylic paints, latex paints, enamels, varnishes, and water-based sealers. For occasional use with solvent-based paints containing turpentine.

Do not use thinner.

Not recommended for use with industrial paints.



New look
Even bolder and
more modern



Now with voltmeter

The new D-3X has a voltage reader
that provides even more safety to
the equipment

	HEIGHT	LENGTH	WIDTH
PACKAGING DIMENSIONS	51cm	53,5cm	41,5cm

ADDITIONAL DATA

ENGINE POWER	1,8 hp
MAXIMUM FLOW RATE	3.6 LITERS/MIN.
MAX TIP SIZE	0,025"
MAXIMUM PRESSURE	3.000 PSI
VOLTAGE	220 VOLTS/60Hz
NET WEIGHT	29,5kg
GROSS WEIGHT	31,8kg
GENERATOR/TRANSFORMER	5 kVA



Assembled in
BRAZIL



Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br