



TECHNICAL SHEET

OPERATIONAL DATA

FT D-5X - 3704
Elaboration date: 01/31/2023
Revision: 11/13/2025-05



D-5X AIRLESS MACHINE

Reference 3704

DESCRIPTION

Airless sprayer with a diaphragm system. Made of steel, galvanized (anti-rust) and powder coated. The shielded motor, with reliable power and performance, generates high production capacity.

High pressure for an excellent finish, better atomization and greater efficiency.



FEATURES

It features heavy-duty wheels for easy transport. It features high-quality valves, a pressure regulator, and a mechanical pressure control valve. The coupling connection to the machine is made of stainless steel.

Includes 1 1/4 15m hose, 1 Nauber Ultra spray gun, 1 Light Green 517 airless tip, 1 Light Green aluminum tip guard, 1 60 mesh white filter and 1 50cm extender.

Maximum hose length: 60 meters.

220 volts/50-60Hz equipment.

INDICATIONS FOR USE

Suitable for painting in construction with acrylic paints, latex, enamels, varnishes and water-based sealers. For occasional use in solvent-based paints. **Not suitable for industrial use.**

ADDITIONAL DATA

ENGINE POWER	3,0 hp
MAXIMUM FLOW RATE	5.0 LITERS/MIN.
MAX TIP SIZE	0,029"
MAXIMUM PRESSURE	3.000 PSI
VOLTAGE	220 VOLTS/60Hz
NET WEIGHT	30,6kg
GROSS WEIGHT	37kg
GENERATOR/TRANSFORMER	5kVA

	HEIGHT	LENGTH	WIDTH
PACKAGING DIMENSIONS	54cm	49cm	61cm



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br