



TECHNICAL SHEET

OPERATIONAL DATA

FT N-30:1 - 1048
Elaboration date: 01/14/2023
Revision: 05/24/2025-03



N-30i PNEUMATIC EQUIPMENT

Reference 1048

DESCRIPTION

Airless painting equipment with pneumatic motor.
High-performance pumping and pressurization.
Works with up to 3 guns.
Equipped with a filter regulator and lubricator, which facilitates air control, filtration and lubrication, extending the useful life and improving equipment performance.
Stainless steel pump with PTFE and leather gaskets and seals, providing durability and high performance.

FEATURES

Flow rate of up to 6.5 liters/min.
Working pressure of 3,400 PSI.
Equipped with filter regulator and lubricator.
Compression ratio: 30:1.
180mm pneumatic motor assembly.
With trolley for transportation.
Noise level of only 75 decibels.
3/4 ar entrance.

INDICATIONS FOR USE

Suitable for painting applications with industrial, synthetic or acrylic paints.
Ideal for applications in naval painting, metal structures, power plants, silos and other applications that require coverage with high thickness and solids content paints and coatings.



	HEIGHT	LENGTH	WIDTH
PACKAGING DIMENSIONS	102cm	63cm	57cm

RATIO	30:1
MAX AIR PRESSURE	8 bar - 115 PSI
MAX. MATERIAL PRESSURE	240 bar - 3,400 PSI
PUMP CAPACITY	6.5 LITERS/MIN.
GROSS WEIGHT	47,45kg
COMPRESSOR INDICATION	7 bar/10 ft flow rate



Assembled in
BRAZIL



Record
172951-7



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br