



# TECHNICAL SHEET

## OPERATIONAL DATA

FT N-3i - 4491  
Elaboration date: 01/14/2023  
Revision: 05/24/2025-03



# N-3I AIRLESS MACHINE

Reference 4491

## DESCRIPTION

The shielded motor, with reliable power and performance, generates high production capacity. High pressure for excellent finish, better atomization, and greater efficiency. It features high-quality valves, a pressure regulator, and a mechanical pressure control valve.

With a cart that makes transportation easier.



## FEATURES

Lightweight and compact. Features heavy-duty wheels for easy transport. Features high-quality valves, a pressure regulator, and a mechanical pressure control valve. Stainless steel coupling connection to the machine.

Maximum hose length:

60 meters.

Includes 1 1/4 15m hose, 1 Nauber Ultra Industrial spray gun, 1 Light Green 517 airless tip, 1 Light Green aluminum tip guard, 1 60 mesh white filter and 150cm extender.

**220 volts/60Hz equipment.**



## INDICATIONS FOR USE

Ideal for medium-sized industries.

	HEIGHT	LENGTH	WIDTH
PRODUCT MEASUREMENTS	74cm	39,2cm	44cm
PACKAGING DIMENSIONS	54cm	49cm	61cm

## ADDITIONAL DATA

ENGINE POWER	1,8hp
MAXIMUM FLOW RATE	3.0 LITERS/MIN.
MAX AIRLESS TIP SIZE	0,027"
MAXIMUM PRESSURE	3.000 PSI
VOLTAGE	220 VOLTS/60Hz
NET WEIGHT	27,5kg
GROSS WEIGHT	31,8kg
GENERATOR/TRANSFORMER	3 kVA



Email  
atendimento@nauber.com.br



Telephone  
+55 47 33745969



Web Site  
www.nauber.com.br