



TECHNICAL SHEET

OPERATIONAL DATA

FT N-80:1 - 1532
Elaboration date: 01/14/2023
Revision: 05/24/2025-03



N-80i PNEUMATIC EQUIPMENT

Reference 1532

DESCRIPTION

Airless paint sprayer with pneumatic motor. High-performance pumping and pressurization.

Works with up to 3 guns.

Equipped with a filter regulator and lubricator, which facilitates air control, filtration, and lubrication, extending the lifespan and improving the performance of the equipment.

Stainless steel pump with PTFE and leather seals and gaskets, providing durability and high performance.

FEATURES

Flow rate up to 25 liters/min.

Working pressure of 9,282 PSI.

Equipped with filter regulator and lubricator.

Compression ratio: 80:1.

280mm air motor assembly.

With cart for transport.

Noise level of only 75 decibels.

3/4 ar entrance.

INDICATIONS FOR USE

Suitable for painting applications with industrial, synthetic or acrylic paints.

Ideal for applications in naval painting, metal structures, power plants, silos, and other applications requiring coverage with high-build, high-solids paints and coatings.



	HEIGHT	LENGTH	BROAD
PACKAGING DIMENSIONS	105cm	70cm	56cm

ADDITIONAL DATA

RATIO	80:1
MAXIMUM AIR PRESSURE	8 bars - 115 PSI
MAXIMUM MATERIAL PRESSURE	640 bars - 9282 PSI
PUMP CAPACITY	25 LITERS/MIN.
GROSS WEIGHT	93,55 kilos
COMPRESSOR INDICATION	Flow rate of 7 bar/20 ft



Assembled in
BRAZIL



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Website
www.nauber.com.br