



TECHNICAL SHEET

OPERATIONAL DATA

FT N-3i MAX - 2261
Elaboration date: 07/20/2023
Revision: 05/24/2025-03



N-3I MAX AIRLESS MACHINE

Reference 2261

DESCRIPTION

The shielded motor, with reliable power and performance, generates high production capacity. High pressure for excellent finish, better atomization, and greater efficiency. It features high-quality valves, a pressure regulator, and a mechanical pressure control valve. With a cart that makes transportation easier.



RESERVOIR DESCRIPTION

Made of PVC, with a filter system at the top. Capacity up to 30 liters. With a screen for paint filtration.

ADVANTAGES:

- ease of suction;
- upper screen that facilitates the preparation of quality material;
- Possibility of placing 02 pistols.

FEATURES

Lightweight and compact. Features heavy-duty wheels for easy transport. Features high-quality valves, a pressure regulator, and a mechanical pressure control valve. Stainless steel coupling connection to the machine. Maximum hose length: 60 meters. Includes 11/4 15m hose, 1 Nauber Ultra Industrial spray gun, 1 Light Green 517 airless tip, 1 Light Green aluminum tip guard, 160mesh white filter and 150cm extender. **220 volts/60Hz equipment.**

	HEIGHT	LENGTH	WIDTH
PACKAGING DIMENSIONS	54CM	49CM	61CM



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br