



TECHNICAL SHEET

OPERATIONAL DATA

FT STRIKE MASK - 808
Elaboration date: 01/14/2023
Revision: 05/23/2025-03



STRIKE PAINTING MASK

Reference 808

DESCRIPTION

Excellent quality material, comfortable and safe.

CHARACTERISTICS

High-strength acrylic transparent visor with excellent visibility, anti-fog and shockproof system.

Mask with triple filtration system.

PRECAUTIONS

1. The mask should be inspected before each use to ensure it is in good condition. Before use, if there are any damaged or defective parts, they should be replaced.
2. If exhalation resistance increases or the filter is dirty or damaged, leave the polluted area immediately.
3. Replace the filter before returning to the location.
4. This mask must be used with the corresponding filter cartridge for each application and work environment.



(The mask does not include a filter, as filter installation requires verifying the protective properties for the workplace. Specific filters, with or without activated carbon, are necessary for each application.)

	HEIGHT	LENGTH	WIDTH
PACKAGING MEASUREMENTS	22,5cm	19,5cm	13,5cm

INDICATIONS FOR USE

In environments involving painting, cutting, chemicals, industrial products, etc.

ADDITIONAL DATA

GROSS WEIGHT	0,671kg
--------------	---------



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br