



TECHNICAL SHEET

OPERATIONAL DATA

FT TK100P 1.2/1.4
Elaboration date: 14/01/2023
Revision: 24/05/2025-04



TK100P NAUBER SPRAY GUN

DESCRIPTION

Reference 2161 (1.2mm) / 2162 (1.4mm)

The NAUBER TK100P spray gun offers excellent ergonomics, is lightweight, and easy to operate.

High durability under high production conditions makes the TK100P a unique product.

Featuring an LVLP painting system, it offers excellent finish quality and high performance designed for high-volume production.

It provides a fan formation with less air volume, preventing paint smudges.

BENEFITS:

- Fog reduction
- It increases productivity.
- Application speed
- Minimum maintenance cost
- High-Transfer System
- Very light
- Low air consumption
- Ergonomic design
- Easy to use
- Fast amortization

CHARACTERISTICS

Sistema LVLP.

Stainless steel body with balanced air cap.

Multifuro ar layer.

Machined Teflon fence.

Easy maintenance.

Nozzle and needle made of highly durable material.

Includes disassembly wrench and cleaning brush.

INDICATIONS FOR USE

Furniture industry, metalworking, agricultural and road equipment, among others.



MULTIFUNCTIONAL
AR LAYER

| | HEIGHT | LENGTH | WIDTH |
|------------------------|--------|--------|--------|
| PACKAGING MEASUREMENTS | 5cm | 23cm | 14,5cm |

ADDITIONAL DATA

| | |
|--------------------|---|
| AIR CONSUMPTION | 392 LITERS/MIN. |
| MAXIMUM PRESSURE | 3.9 - 4.9 bar (56 - 71 PSI) |
| AVAILABLE TIPS | 1.0mm / 1.2mm / 1.3mm / 1.4mm / 1.5mm / 1.8mm / 2.0mm |
| AIR CONNECTION | M 1/4" NPS |
| PRODUCT CONNECTION | M 1/4" NPS |
| GROSS WEIGHT | 0,445kg |



Email
atendimento@nauber.com.br



Telephone
+55 47 33745969



Web Site
www.nauber.com.br