



# TECHNICAL SHEET

## OPERATIONAL DATA

FT NAUBER TIP GUARDS  
Elaboration date: 01/14/2023  
Revision: 12/09/2025-05



# AIRLESS NAUBER TIP GUARDS

Reference see below

## NICKEL PLATED

### DESCRIPTION

Tip guard with standard 7/8 nickel-plated thread.

### CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm.  
It withstands pressure up to 5.000 PSI.



Reference: 5422

Reference: 4549



## STAINLESS STEEL

### DESCRIPTION

Tip guard with standard 7/8 stainless steel thread.

### CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm.  
It withstands pressure up to 7.250 PSI.



Reference: 4229

Reference: 4230



## ALUMINUM

### DESCRIPTION

Tip guard with standard 7/8 aluminum thread.

### CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm.  
It withstands pressure up to 7.250 PSI.

## UHD

### DESCRIPTION

Tip guard with standard 7/8 stainless steel thread.

### CHARACTERISTICS

Compatible with airless tips with a stem diameter of 11,1mm.  
It withstands pressure up to 7.250 PSI.

## INSTRUCTIONS FOR USE (ALL MODELS)

For use in airless painting systems.

PACKAGING DIMENSIONS	HEIGHT	LENGTH	WIDTH
ALL MODELS	15,1cm	9cm	3,5cm
GROSS WEIGHT			
ALL MODELS	65g		



**CREA-SC**  
Record  
172951-7



Email  
atendimento@nauber.com.br



Telephone  
+55 47 33745969



Web Site  
www.nauber.com.br